


SPEKTRUM®

DX7

**7-Channel, 20-Model Memory
Full Range DSM2™ System**



Welcome to the World of Spektrum DSM2 Full Range Technology

Spektrum's DX7 is the first-ever full range 2.4Ghz Spread Spectrum Radio system for R/C aircraft. With Spektrum's DSM2™ technology, now even large gas- and glow-powered aircraft can take advantage of Spektrum® technology. No longer will you have to wait for a frequency pin or be concerned that someone may inadvertently turn on to your same frequency. With Spektrum DSM2 technology, when you're ready to fly any aircraft—from parkflyer to giant-scale—simply turn on the system, and go flying!



DSM2 DualLink Technology


Your DX7 transmits on the 2.4GHz band and utilizes DSM2™ second-generation Digital Spread Spectrum Modulation giving visual range in all types and sizes of aircraft. Unlike conventional narrow band systems, Spektrum's 2.4GHz digital DualLink™ technology is virtually immune to internal and external radio interference.

Included with your DX7 is an AR7000 7-channel receiver. The AR7000 combines an internal and external receiver, offering superior path diversity. The system simultaneously transmits on two frequencies, creating dual RF paths. This dual path redundancy, plus the fact that each of the two receivers is located in a slightly different location exposes each to a different RF environment and creates a bulletproof RF link in all conditions.



AR6000 Parkflyer Compatible

You'll be glad to know that the DX7 is compatible with the AR6000 mini park flyer receiver, however, when using the AR6000 receiver, aircraft type is limited to parkflyers and mini and micro helicopters only. Simply bind the DX7 transmitter to the AR6000 and you are ready to fly.



Model Match

With patented Model Match™ technology, you'll never mistakenly try to fly your model using the wrong memory again. The DX7 features Model Match technology that prevents the operation of a model if the wrong model memory is selected. During binding, the receiver actually learns and remembers the specific model memory (1 of 20) that the transmitter is currently programmed to. Later, if the incorrect model is selected in the transmitter and the receiver is turned on, the model simply won't operate preventing a possible crash. Change programming to the matching model memory and you are set to fly.

Using This Manual

For your convenience, this manual is arranged with separate sections for airplane and helicopter software functions. Airplane Programming is located on Pages 27 through 61; Helicopter Programming is located on Pages 63 through 97. Programming functions are discussed in the same order that they appear on the radio. An explanation of the use and purpose of each feature is provided, followed by an illustration of its LCD display. A blank data sheet has been included at the end of each section. Once all data has been input for a particular model, it is highly recommended that you also record it on a copy of the data sheet provided.

Alternate Languages

ITALIAN: Per la versione italiana di questo manuale vi preghiamo di visitare il sito www.spektrumrc.com

FRENCH: Pour consulter ce manuel en français, visiter le site www.spektrumrc.com

GERMAN: Zur Ansicht der Bedienungsanleitung in den Deutsch besuchen Sie bitte www.spektrumrc.com

SPANISH: Para ver este manual en Español entra en www.spektrumrc.com

Table of Contents

Welcome to the World of Spektrum DSM2 Full Range Technology	2
DSM2 DualLink Technology	3
AR6000 Parkflyer Compatible	3
Model Match.....	4
Using This Manual.....	4
Alternate Languages.....	4
Battery Charging.....	10
Transmitter/Receiver	10
Transmitter Polarity.....	10
Charger.....	10
Control Stick Tension Adjustment.....	11
Removing the Back of the Transmitter	11
Adjusting the Control Stick Tension.....	12
Control Stick Length Adjustment	12
Screen Contrast	13
Advanced Digital Trims	13
Receiver and Servo Installation.....	14
Receiver Installation.....	15
Servo Installation.....	17
How to Range Test the DX7	17
Range Testing the DX7.....	17
Binding	18
SmartSafe Fail Safe.....	18
Airplane Quick Start.....	20
Model Type Selection.....	20
Selecting Airplane Mode.....	20
Servo Reversing.....	21
To Access Servo Reversing.....	21
Travel Adjust	22
To Access Travel Adjust	22
Helicopter Quick Start.....	23
Model Type Selection.....	23
Selecting Helicopter Mode.....	23
Servo Reversing.....	24
To Access Servo Reversing.....	24
Travel Adjust	24
To Access Travel Adjust	24
Pitch Curve.....	25
Adjusting the Normal Pitch Curve.....	25
To Access the Pitch Curve Function.....	25
Throttle Curve.....	26
Adjusting the Normal Throttle Curve.....	26
To Access the Throttle Curve Function.....	26

Table of Contents

Aircraft Programming Guide	27
Control Identification and Location - Airplane Mode 2.....	27
Throttle ALT	27
General Information	28
Key Input and Display Functions	28
System Mode Functions	29
System Mode.....	29
To Enter the System List Mode	29
System Setup Mode Flowchart.....	30
To Enter the System Setup Mode	30
To Exit the System Setup Mode	30
Model Select/Copy Function	31
To Enter the Model Select Function	31
Model Match	31
How Model Match Works	31
To Enter the Copy Function.....	32
Model Name	33
To Enter the Model Name Function.....	33
Model Match	33
How Model Match Works	33
Type Select Function.....	34
To Enter the Type Select Mode.....	34
To Select a Model Type.....	34
Model Reset and Integrated Timer Reset.....	35
To Perform a DATA RESET or Reset the Integrated Timer:.....	35
Trainer.....	36
To Enter the Trainer Mode	36
Throttle Recovery.....	37
To Activate Throttle Recovery.....	37
Input Select.....	38
To Access Input Select	38
Wing Type.....	39
Normal.....	39
Flaperon Wing Type Selection	39
Delta Wing Type Selection	39
To Enter the Wing Type Function	39
To Select a Wing Type.....	40
Flaperon Wing Type Servo Connections.....	41
Delta Wing Type Servo Connections.....	41
V-Tail Type Servo Connections	41
Function Mode	42
To Enter Function Mode.....	42
Function Mode Flowchart	43
Function List Modes	44
To Enter the Function List Mode	44
To Exit the Function List Mode	44

Table of Contents

Dual Rate and Switch Select	45
To Activate Dual Rate and Switch Select	45
Function Mode Functions	46
Dual Rate and Exponential	46
To Adjust the Dual and Expo Rates	46
To Adjust the Exponential	47
Reverse Switch	48
To Access the Reverse Switch Mode	48
Sub-Trim.....	49
To Access the Sub-Trim Function	49
Travel Adjust	50
To Access the Travel Adjust Function.....	50
Elevator-to-Flap Mix Function	51
To Access the Elevator-to-Flap Mixing.....	51
To Select the Switch to Operate the Flap Mix	51
Aileron-to-Rudder Mixing.....	52
To Access the Aileron-to-Rudder Mix Function	52
To Adjust the Mix Value	52
To Assign a Switch	52
Flap System	53
Accessing and Utilizing the Flap System	53
Automatic Landing.....	54
To Activate the Automatic Landing Feature	54
Differential Aileron Mixing.....	55
To Access the Differential Aileron Mixing Function.....	55
Programmable Mixing 1–6.....	56
Assigning Channels.....	57
Assigning Mixing Values.....	57
Assigning an Offset.....	58
Assigning a Switch	58
Timer	59
Servo Monitor.....	61
Helicopter Programming Guide.....	63
Transmitter Control Identification and Location.....	63
General Information	64
Key Input and Display Functions	64
Warning Screen for Throttle Hold/Stunt Mode.....	65
Gyro Connections.....	65
System Setup Mode.....	66
To Enter the System Setup Mode	66
To Exit the System Setup Mode	66
Model Select/Copy	67
To Enter the Model Select Function	67
To Enter the Copy Function.....	67

Table of Contents

Model Name	68
To Enter the Model Name Function	68
Model Match	68
How Model Match Works	68
Type Select Function	69
To Enter the Type Select Mode	69
To Select a Model Type	69
Model Reset/Integrated Timer	70
To Reset a Model	70
To Reset the Integrated Timer	70
Trainer	71
To Enter the Trainer Mode	71
Throttle Recovery	72
To Activate the Throttle Recovery Function	72
Input Select	73
To Select the Function for the AUX2 Channel	73
To Select the Function for the Gear Channel	74
Swash Type	75
Accessing the Swashplate Types	75
Function Mode Flowchart	76
To Enter the Function Mode	77
To Exit the Function Mode	77
List Modes	78
Function Mode Functions	79
Dual Rate and Exponential	79
To Adjust the Dual Rate	79
To Adjust the Exponential	80
Auto Dual Rate EXP	81
To Adjust the Auto Dual Rate	81
Reverse Switch	82
Accessing the Reverse Switch Function	82
Sub Trim	83
To Access the Sub-Trim Function	83
Travel Adjust	84
To Access the Travel Adjust Function	84
Swashplate Mixing	85
Accessing the Swashplate Mix Function	85
Throttle Hold	86
To Access the Throttle Hold Function	86
To Access the Throttle Hold Switch Function	86

Table of Contents

Throttle Curve.....	87
To Access the Throttle Curve Function.....	87
Throttle Trim Setting.....	88
Hovering Throttle Rocker Setting.....	88
Exponential Throttle Curve Function.....	88
Idle Up.....	88
Stunt 1 and Stunt 2.....	88
Pitch Curve.....	89
To Access the Pitch Curve Function.....	89
Hovering Pitch Rocker.....	89
Revolution Mixing (only used with non-heading hold gyros).....	90
Setting Up Revolution Mixing.....	90
To Access Revolution Mixing.....	90
Gyro Sensing.....	91
To Access the Gyro Sensing Function.....	91
Manual Gyro Sensitivity Adjustment.....	91
Automatic Gyro Sensitivity Adjustment.....	91
Programmable Mixing 1–3.....	92
Assigning Channels.....	92
Assigning Mixing Values.....	93
Assigning an Offset.....	94
Timer.....	95
To Access the Timer Function.....	96
Servo Monitor.....	97
General Information.....	99
FCC Information.....	99
Instructions for Disposal of WEEE by Users in the European Union.....	99
Servo Precautions.....	100
General Notes.....	100
Safety Do's and Don'ts for Pilots.....	100
Federal Aviation Administration.....	101
Purpose.....	101
Background.....	101
Operating Standards.....	101
Information Provided By.....	101
Daily Flight Checks.....	102
Three Year Warranty Period.....	103
Limited Warranty.....	103
Damage Limits.....	103
Safety Precautions.....	103
Questions, Assistance, and Repairs.....	104
Inspection or Repairs.....	104
Warranty Inspection and Repairs.....	104
Non-Warranty Repairs.....	104
Aircraft Programming Guide.....	106
Helicopter Programming Guide.....	107

Battery Charging



Transmitter/Receiver

It is imperative that you fully charge both the transmitter and the receiver battery packs prior to each flying session. To do so, using the included wall charger, leave the charger and batteries connected overnight (16 hours).

The charger supplied with this system is designed to recharge your batteries at a rate of 110mA for the transmitter and 110mA for the receiver battery pack.

Transmitter Polarity

The center pin on all Spektrum® transmitters is negative. Therefore, the center pin on all Spektrum chargers is negative, not positive. This is different from many other manufacturers' chargers and radio systems. Beware of improper connections based on "color coded" wire leads, as they may not apply in this instance. You must make sure that the center pin of your Spektrum transmitter is always connected to the negative voltage of your charger for correct polarity hookup.




Charger

The pilot lamps should always be ON during the charging operation. If they're not, check to make sure that both the transmitter and receiver are switched OFF. Do not use this charger for equipment other than Spektrum. The charging plug polarity may not be the same and equipment damage can result. During the charging operation, the charger's temperature is slightly elevated. This is normal.

Control Stick Tension Adjustment

Removing the Back of the Transmitter

Remove the battery cover by pressing down on the ridged areas of the cover and sliding the cover towards the bottom of the transmitter. Unplug the battery and set it aside. Carefully remove the screws from the back of the transmitter using a small Phillips screwdriver.




CAUTION: THE BATTERY CONNECTOR IS KEYSO THAT IT CAN ONLY BE PLUGGED IN ONE DIRECTION. DO NOT FORCE.

Note: Use care when installing the screws securing the back of the transmitter. They are threading into plastic and can be stripped if over-tightened.

Adjusting the Control Stick Tension


Note: Remove the six (6) transmitter back cover screws. Remove the transmitter back, being careful not to cause damage to any components.

Adjust each stick tension screw for the desired tension (counterclockwise to loosen stick tension, clockwise to tighten stick tension).




Control Stick Length Adjustment

The DX7 allows you to adjust the control stick's length. Use the 2mm Allen wrench (supplied with your DX7 transmitter) to unlock the setscrew. Turn the wrench counterclockwise to loosen the screw. Then, turn the stick clockwise to shorten or counterclockwise to lengthen. After the control stick length has been adjusted to suit your flying style, tighten the 2mm setscrew.



Screen Contrast

The screen contrast is adjustable, allowing the user to vary the contrast for improved clarity in all conditions. To adjust contrast: With the transmitter on and in the main menu, press and hold the select key. Then pressing the **INCREASE** or **DECREASE** key will lighten or darken the contrast.




Advanced Digital Trims

The DX7 employs digital trim levers on aileron, elevator, throttle, and rudder. (Hover pitch and hover throttle for helicopters). The ADT (Advanced Digital Trim) feature is designed to automatically store the selected trim values for each model. When a different model is selected, the previously stored trim positions for that model are automatically recalled.


When using the helicopter program, each flight mode has its own trim that is automatically recalled each time that flight mode is entered.

Visual trim positions are displayed on the main screen. The trims feature dual speed scrolling. Holding the trim lever for an extended time will cause the trim rate of change to increase.



Receiver and Servo Installation

The AR7000 incorporates dual receivers, offering the security of dual path RF redundancy. An internal receiver is located on the main PC board, while a second external receiver is attached to the main board with a 6" extension. By locating these receivers in slightly different locations in the aircraft, each receiver is exposed to its own RF environment, greatly improving path diversity (the ability for the receiver to see the signal in all conditions).



Receiver Installation

Install the main receiver using the same method you would use to install a conventional receiver in your aircraft. Typically, wrap the main receiver in protective foam and fasten it in place using rubber bands or Velcro straps. Alternately, in electric models or helicopters, it's acceptable to use thick double-sided foam tape to fasten the main receiver in place.



Mounting the remote receiver in a slightly different location, even just inches away from the primary receiver, gives tremendous improvements in path diversity. Essentially, each receiver sees a different RF environment and this is key to maintaining a solid RF link, even in aircraft that have substantial conductive materials (i.e. larger gas engines, carbon fiber, pipes, etc.), which can attenuate the signal.

Using servo tape, mount the remote receiver keeping the remote antennas at least 2" away from the primary antenna. Ideally, the antennas will be oriented perpendicularly to each other, however, we've found this to not be critical. In airplanes, we've found it best to mount the primary receiver in the center of the fuselage on the servo tray and to mount the remote receiver to the side of the fuselage or in the turtle deck.




Receiver Installation (continued)

In helicopters, there is generally enough room on the servo tray to achieve the necessary separation. If necessary a mount can be fashioned using clear plastic to mount the external receiver.



Servo Installation

In gas- and glow-powered aircraft where vibration is present, the servos should be mounted using the supplied rubber grommets and bushings. Do not over-tighten the mounting screws. The diagram will assist you in properly mounting the grommets and bushings. In electric and non-powered aircraft, there are many acceptable methods for mounting the servo, including servo tape and even glue. See the information included with your aircraft for the recommendation for installing servo(s) in your aircraft.




How to Range Test the DX7

Before each flying session, and especially with a new model, it is important to perform a range check. The DX7 incorporates a range testing system which, when the bind button on the back of the transmitter is pressed and held, reduces the output power, allowing a range check.



Range Testing the DX7

1. With the model resting on the ground, stand 30 paces (approx. 90 feet) away from the model.
2. Face the model with the transmitter in your normal flying position and depress and hold the bind button on the back of the transmitter. This causes reduced power output from the transmitter.
3. You should have total control of the model with the button depressed at 30 paces (90 feet).
4. If control issues exist, call the Spektrum Service Center at 1-877-504-0233 for further assistance.



Binding

The AR7000 receiver must be bound to the transmitter before it will operate. Binding is the process of teaching the receiver the specific code of the transmitter so it will connect to that specific transmitter. Once bound, the receiver will only connect to the transmitter when the previously bound model memory is selected. If another model memory is selected, the receiver will not connect. This feature is called Model Match and prevents flying a model using the wrong model memory.

SmartSafe Fail Safe


The AR7000 features the SmartSafe™ fail-safe system.

SmartSafe:


- Prevents unintentional electric motor response on start-up.
- Eliminates the possibility of overdriving servos on start-up.
- Establishes low-throttle failsafe if the RF signal is lost.
- Maintains last-commanded control surface position in the event of RF link interruption.

Note: Fail-safe positions are stored via the stick and switch positions on the transmitter during binding.


1. With the system hooked up as shown, insert the bind in the charge plug receptacle.




2. Turn on the receiver switch. Note that the LED's on both receivers should be flashing, indicating that the receiver is ready to bind.




3. Establish the desired fail-safe stick positions: normally low throttle and flight controls neutral.



4. Press and hold the bind button on the back of the transmitter while turning on the power switch. The bind button should flash and within a few seconds the system should connect. The LED's on the receivers should go solid indicating the system has connected.



5. Remove the bind button and store it in a convenient place.




6. After you've programmed your model, it's important to rebind the system so the true low throttle and neutral control surface positions are programmed.

Note: The AR7000 features DSM2™ technology and is only compatible with DSM2 transmitters. The AR7000 will not operate with the DX6 or Spektrum® surface systems.

Airplane Quick Start

The following covers a basic 4-channel airplane with a single rate. For more details on programming for the aircraft mode, see the Aircraft section of this manual.

Model Type Selection



Selecting Airplane Mode

Press the **DOWN** and **SELECT** keys simultaneously and hold while turning on the transmitter to enter System Setup mode.


Press the **UP** or **DOWN** button until **TYPE SELECT** appears on screen.

If **ACRO** is highlighted on screen, proceed to **SERVO REVERSING**. (Page 21)

If **HELI** is highlighted, press the **INCREASE** or **DECREASE** key once and **ACRO** should be highlighted.

Press the **CLEAR** key to accept the model type change.

Servo Reversing




To Access Servo Reversing

Turn the power on, press the **DOWN** and **SELECT** keys simultaneously to enter the function mode.

Press the **UP** or **DOWN** key until **REVERSING SW** appears on screen.

Press the **SELECT** key to select the desired channel, then press the **INCREASE** or **DECREASE** key to select reverse or normal servo direction.

Travel Adjust



To Access Travel Adjust

Turn the power on and press the **DOWN** and **SELECT** keys simultaneously to enter the function mode.

Press the **UP** or **DOWN** key until **TRAVEL ADJUST** appears on screen. Press the select key to move the cursor arrow to the desired channel.

Use the **SELECT** key to choose the appropriate channel that you wish to adjust.

While holding the channel or switch in the desired direction, press the **INCREASE** or **DECREASE** key to adjust the travel adjust in that direction.


This completes the basic Quick Start setup for your airplane. For additional features like Dual and Expo rates, Mixing, etc, see the appropriate pages listed in the table of contents.

Note: If your airplane's ailerons are controlled independently by two servos, see "Wing Type Selection" on Page 39 for specifics on programming flaperons.

Helicopter Quick Start

The following covers a basic 5-channel mechanical mix helicopter with single rate. For more details on programming for the helicopter mode, see the Helicopter section of this manual.

Model Type Selection



Selecting Helicopter Mode

Press the **DOWN** and **SELECT** keys simultaneously and hold while turning on the transmitter to enter system set up mode.


Press the **UP** or **DOWN** button until **TYPE SELECT** appears on screen.

If **HELI** is highlighted on screen, proceed to **SERVO REVERSING**. (Page 24)

If **ACRO** is highlighted, press the **INCREASE** or **DECREASE** key once and heli should be highlighted.

Press the **CLEAR** key to accept the model type change.

Servo Reversing




To Access Servo Reversing

Turn the power on and press the **DOWN** and **SELECT** keys simultaneously to enter the function mode.

Press the **UP** or **DOWN** key until **REVERSING SW** appears on screen.

Press the **SELECT** key to select the desired channel then press the **INCREASE** or **DECREASE** key to select **REVERSE** or **NORMAL** servo direction.

Travel Adjust



To Access Travel Adjust

Turn the power on and press the **DOWN** and **SELECT** keys simultaneously to enter the function mode.


Press the **UP** or **DOWN** key until **TRAVEL ADJUST** appears on screen.

Press the **SELECT** key to select the desired channel, then press the **INCREASE** or **DECREASE** key while holding the stick or switch in the desired direction that you wish to adjust the servo travel.

Pitch Curve

Adjusting the Normal Pitch Curve

The DX7 offers four independent pitch curves, each with up to five adjustable points. This function allocates a separate pitch curve setting during normal, stunt 1, stunt 2 and hold modes. Once the pitch curves are adjusted, each can be activated in flight using the three-position flight mode and throttle hold switches. Each of the five points of the pitch curve are independently adjustable from 0–100%. These five points correspond to low, 25%, mid, 75% and high stick positions. See Page 89 for more details on setting up pitch curves.



To Access the Pitch Curve Function

Turn the power on and press the **DOWN** and **SELECT** keys simultaneously to enter the function mode.

Press the **UP** or **DOWN** key until **PITCH CURVE NORM** appears on screen.

Press the **SELECT** key to select the stick position that you wish to adjust the pitch.

- L= Low
- 1= 25%
- 2= 50%
- 3= 75%
- H= High

Press the **INCREASE** or **DECREASE** keys to adjust the pitch value of the selected pitch position.

Recommended Initial Pitch Settings


- L= -4°
- 2= 5°
- H= 9°

Note: For more information about setting up pitch curves, see Page 89.

Throttle Curve

Adjusting the Normal Throttle Curve

Adjustment of the throttle curves is similar to the pitch curve adjustment described on the preceding page. Three throttle curves are available: normal, stunt 1 and stunt 2. All throttle curves have five adjustable points—low, 25%, 50%, 75% and high. Flight modes are located on the 3-position flight mode switch. The throttle curve is in the normal mode when the Flight Mode switch is in the rear position and the Throttle Hold switch is rearward.



To Access the Throttle Curve Function

Turn the power on and press the **DOWN** and **SELECT** keys simultaneously to enter the function mode.

Press the **UP** or **DOWN** key until **THROTTLE CURVE NORM** appears on screen.

Press the **SELECT** key to select the stick position that you wish to adjust the throttle.

- L= Low
- 1= 25%
- 2= 50%
- 3= 75%
- H= High

Press the **INCREASE** or **DECREASE** keys to adjust the throttle value of the selected throttle position.

Note: For more information about setting up Throttle Curves see Page 87.


This completes the basic Quick Start setup for your helicopter. For additional features like Dual and Expo Rates, Mixing, etc, see the appropriate pages listed in the table of contents.

Aircraft Programming Guide


Control Identification and Location - Airplane Mode 2

Throttle ALT

The Throttle ALT function makes the throttle stick trim active only when the throttle stick is at less than half throttle. This allows accurate idle adjustments without affecting the mid to high throttle position.



General Information




Key Input and Display Functions

- The **UP** and **DOWN** keys are used to select the programming function.
- The **SELECT** key is used to select the channel or feature that you wish to program.
- The **INCREASE** or **DECREASE** keys are used to change the values of the selected programming feature.

The DX7 features two programming modes: System Mode and Function Mode.

System Mode Functions

System Mode



To Enter the System List Mode

With the transmitter off, press and hold the **DOWN** and **SELECT** keys simultaneously while turning the power switch on to enter the System Mode.

While in the System Mode, press the **UP** and **SELECT** keys simultaneously to access the “List” mode.

Use the **UP** and **DOWN** keys to Scroll through the available function.

Press **DOWN** and **SELECT** to enter a selected function.



In this mode, servos are not activated.

By pressing the **DOWN** and **SELECT** keys twice simultaneously, you can return to the main screen.

System Setup Mode Flowchart

The list mode screens display all the functions onscreen allowing the access of any function without having to scroll through each screen. Note that there are two list modes: a System Setup List Mode that displays all the system setup functions, and a Function List Mode that displays all the system setup functions.

System Mode includes programming functions that are normally used during set up. System programming functions for airplanes include:



Hold while turning on transmitter to enter System Mode

To Enter the System Setup Mode


- With the power switch off, press and hold the **DOWN** and **SELECT** keys simultaneously.
- Turn on the power switch.
- The system will display the last screen that was used in system set up mode. You are now in System Mode.

To Exit the System Setup Mode

- Press the **DOWN** and **SELECT** keys simultaneously. The main screen will be displayed.
- Turn the transmitter off.

Model Select/Copy Function

The DX7 features a memory function that stores the programmed data for up to 20 models. Any combination of up to 20 airplanes and/or helicopters can be stored in memory. A model name feature with up to eight characters allows each model to be easily identified. (See Page 33)



To Enter the Model Select Function

Press the **DOWN** and **SELECT** keys simultaneously and turn the power switch ON to access the System Setup Mode. Press the **INCREASE** or **DECREASE** key until the **MODEL SELECT** screen appears.

Press the **INCREASE** or **DECREASE** key to select the desired model memory.

Model Match


The DX7 features patented Model Match™ technology that prevents operating a model using the wrong memory. This feature can prevent stripped servo gears, broken linkages and even a crash due to trying to operate/ fly a model using the wrong memory.

How Model Match Works

Each individual model memory has its own embedded code that is transferred to the receiver during binding. The receiver actually learns the code for the specific model memory that has been selected during binding and, when bound, will only operate when that model memory is selected. If a different (non-matching) model memory is selected, the receiver simply won't connect. This feature prevents trying to operate/ fly a model using the wrong model memory. The receiver can be re-programmed to operate with any other model memory by simply re-binding with the transmitter programmed to the desired model memory.

Note: If the receiver is turned on and the matching model memory is not selected, the system will not connect. Either select the matching model memory or rebind the receiver in the current model memory to resume operation.

Model Select/Copy Function (continued)



To Enter the Copy Function

Press the **DOWN** and **SELECT** keys simultaneously and turn the power switch ON to access the System Setup Mode.

Press the **UP** or **DOWN** key until Model Select appears on screen.

Press the **SELECT** button to enter the **COPY SCREEN**.


Press the **INCREASE** or **DECREASE** keys to select the model that you wish to copy the model to.

Press the **CLEAR** key to copy the model to the selected model memory.

Note: Be aware that the model you copy to will have its memory replaced with the new model's memory, and the programming information for the model to be copied to will be erased.

Model Name

The Model Name function is used to input and assign the model's name to a specific memory, allowing easy identification of each model's program. Each model's name is displayed on the main screen when that model is selected. Up to eight characters that include numbers and letters are available.



To Enter the Model Name Function

Press the **DOWN** and **SELECT** keys simultaneously, then turn on the transmitter.

Press the **INCREASE** or **DECREASE** key until the **MODEL NAME** screen appears.

Press the **SELECT** key to move the cursor to the desired character's position.

Press the **INCREASE** or **DECREASE** key to select the desired character.

Model Match

The DX7 features patented Model Match™ technology that prevents operating a model using the wrong memory. This feature can prevent stripped servo gears, broken linkages and even a crash due to trying to operate/ fly a model using the wrong memory.


How Model Match Works

Each individual model memory has its own embedded code that is transferred to the receiver during binding. The receiver actually learns the code for the specific model memory that has been selected during binding and, when bound, will only operate when that model memory is selected. If a different (non-matching) model memory is selected, the receiver simply won't connect. This feature prevents trying to operate/ fly a model using the wrong model memory. The receiver can be re-programmed to operate with any other model memory by simply re-binding with the transmitter programmed to the desired model memory.

Note: If the receiver is turned on and the matching model memory is not selected the system will not connect. Either select the matching model memory or rebind the receiver in the current model memory to resume operation.

Type Select Function


The DX7 features two programming types: Airplane and Helicopter. The DX7 can memorize data for up to 20 models individually and the model type will automatically be stored with each model memory.



To Enter the Type Select Mode

Press the **DOWN** and **SELECT** keys simultaneously, then turn on the transmitter.

Press the **UP** key until the **TYPE SELECT** function appears on screen.



To Select a Model Type

Press the **INCREASE** or **DECREASE** key to toggle between the heli or acro model types.

To accept the new model type press the **CLEAR** key. All settings will be set to the factory defaults.

Model Reset and Integrated Timer Reset

The Model Reset function allows the model memory of the current model to be reset to the factory default setting. This screen also allows the integrated timer to be reset.



To Perform a DATA RESET or Reset the Integrated Timer:

Press the **DOWN** and **SELECT** keys simultaneously then turn on the transmitter.

Press the **UP** or **DOWN** key until **MODEL RESET** appears on the screen.

Use the **SELECT** key to select **DATA RESET** or **INTEG-T**.

When **DATA RESET** is selected, pressing the **CLEAR** key will reset the date to the factory default setting for that model, or if **INTEG-T** is selected, the integrated timer will be reset to 0:00:00.

Trainer

The DX7 offers a programmable Trainer function that allows the transmitter to operate in three different Trainer modes. Either the left or right rocker can be programmed as the trainer switch.

NORMAL:


The transmitter can be used as a master or slave but the slave transmitter must have the same programming (i.e. reverse, travel adjust, dual rates, mixes, sub trims, etc.) as the master.

P-LINK:

In Pilot Link the master transmitter maintains control of all secondary functions (i.e. dual rate, expo, gear, flaps, etc.) and only the primary stick controls (aileron, elevator, rudder and throttle) are transferred to the slave transmitter when the trainer switch is pressed.

SLAVE/P-LINK:

In the Slave mode, the DX7 is used as a slave radio in conjunction with a Spektrum® radio that is used as the master that is in P-LINK mode; there is no need to match the slave's programming to the master transmitter's programming in this mode.



To Enter the Trainer Mode

Press the **DOWN** and **SELECT** keys simultaneously then turn on the transmitter.

Press the **UP** key until **TRAINER** function appears on screen.

Press the **INCREASE** or **DECREASE** key to select the desired Trainer type: **INH**, **NORMAL**, **P-LINK** or **SLAVE/P-LINK**.

Also note that the trainer switch can be located on the right or left rocker switch. Use the **SELECT** key to highlight **SW:R** then press the **INCREASE** or **DECREASE** key to select the **RIGHT (R)** or **LEFT (L)** rocker.

Throttle Recovery

The DX7 has a unique throttle trim recovery feature. Throttle Recovery stores the last known throttle trim position before the trim is moved to the full down (closed) position. That stored position is then recalled by moving the throttle trim up (open) one notch. This makes shutting off the engine and restarting it with the correct trim position easy. Throttle Recovery must be activated for each model.



To Activate Throttle Recovery


Press the **DOWN** and **SELECT** keys simultaneously, then turn on the transmitter.

Press the **UP** key until the **THRO RECOVERY** function appears on screen.

Press the **INCREASE** or **DECREASE** key to turn on/off the throttle recovery function.

Input Select

The purpose of the Input Selection Function is to assign the activation device for the AUX2 channel and the Flap Channel.



To Access Input Select

Press the **DOWN** and **SELECT** keys simultaneously, then turn on the transmitter.

Press the **UP** key until the **INPUT SELECT** function appears on screen.

Here you have 4 choices that can be used to operate the AUX2 channel:

- 2-position switch
- INH
- Rocker
- 3-position switch

(The rocker provides proportional control, while the switch allows 2 or 3 positions of the AUX2 channel. You can also use the rocker for an AUX2 trim switch when using the 2P switch to activate the AUX2 function. Or you can inhibit the AUX2 rocker as well to prevent inadvertent changes.)

In addition, you have 3 choices to activate/inhibit **FLAP SYSTEM**:

- System (3-position switch)
- INH
- Rocker

(The rocker provides proportional control, while the system allows 3-position function of the FLAP channel. You can also use the rocker for a FLAP trim switch when using the 3P switch to activate the FLAP function. Finally, you can inhibit the FLAP Rocker as well to prevent inadvertent changes.)

Note: When operating the transmitter in a trainer mode (Normal or P-Link Master) the Trainer-Flap Rocker is not available to control the flaps.

Note: The individual AUX2/spoiler operation is inhibited when AUX2/spoiler is coupled for automatic landing attitude.

Wing Type

The DX7 offers three different wing types to choose from: Normal, Flaperon and Delta (also called elevon mixing). In addition, V-Tail mixing is available from the Wing Type screen.

Normal


When the Flaperon and Delta wing function are off, Normal wing type is selected. Use this wing type with common aircraft that utilize only one servo for both ailerons. Normal is the default setting.

Flaperon Wing Type Selection

Flaperons require the use of one servo for each aileron and allow the use of ailerons as flaps or spoilers. This function also allows the precise independent adjust of up and down travel, and independent sub-trim and differential of each aileron.

Delta Wing Type Selection

Delta wing arrangements combine the function of ailerons with the function of the elevator to allow precise control of both roll and pitch.




To Enter the Wing Type Function

Press the **DOWN** and **SELECT** keys simultaneously, then turn on the transmitter.


Press the **UP** key until **WING TYPE** function appears on screen.

Wing Type (continued)


Flaperon Active:



V-Tail Active:



Delta Active:



To Select a Wing Type

Press the **INCREASE** or **DECREASE** key until the desired wing type is highlighted on screen: **NORMAL**, **FLAPERON**, **DELTA WING**.


Note: When Flaperon or Delta Wing type is selected, the travel adjustment is used to adjust the individual servo throw, while the combined aileron travel is adjusted with the aileron dual rate. It is also possible to set aileron differential. Reverse switches are applicable for each servo. Neutral adjustments of each servo are made by the Sub Trim Function.

Wing Type (continued)

Flaperon Wing Type Servo Connections

- AILE servo port (right aileron)
- AUX1 servo port (left aileron)


Flaperon Wing Type Connection



Delta Wing Type Servo Connections

- ELEV servo port (right aileron)
- AILE servo port (left aileron)


Delta Wing Type Connection




V-Tail Type Servo Connections

- RUDD servo port (right V-tail)
- ELEV servo port (left V-tail)

V-Tail Type Connection



Function Mode




To Enter Function Mode

- From Main Screen Display press the **DOWN** and **SELECT** keys simultaneously to enter the Function Mode.
- Use the **UP** or **DOWN** keys to select the desired function.
- Use the **SELECT** key to scroll to the desired channel.
- Use the **INCREASE** and **DECREASE** keys to change the values or positions of the selected channel.
- Use the **CLEAR** key is used to return the selected value to the factory default settings.

Function Mode Flowchart

Information pertaining to each function is explained on the following pages. Functions will appear on the screen in the same order they are shown on the flow chart below:




Function List Modes

The list mode screens display all the functions onscreen allowing the access of any function without having to scroll through each screen. Note that there are two list modes: a System Setup List Mode that displays all the system setup functions, and a Function List Mode that displays all the system setup functions.

To enter the Function List Mode, with the system on and in any function mode screen, press the **UP** and **SELECT** keys simultaneously.

In list mode, pressing the **UP** and **DOWN** keys will move the cursor to the desired function. Then pressing the **DOWN** and **SELECT** keys simultaneously will access the selected function.



To Enter the Function List Mode

- Turn the transmitter on.
- From the main screen, press the **UP** and **SELECT** keys simultaneously.
- The system is now in Function List Mode and will display a list of all the functions available.
- Use the **UP** and **DOWN** keys to Scroll through the available function.
- Press **DOWN** and **SELECT** to enter a selected function.


To Exit the Function List Mode

- Press the **DOWN** and **SELECT** keys simultaneously twice. The system will return to the main screen or turn off the transmitter.

Dual Rate and Switch Select

The D/R switch select function allows the dual and expo rates to be selected via individual switches (aileron, elevator and rudder D/R switches) or to be conveniently combined on a single switch. When combined to a single switch the following switch options are available:

- COM AILE: Aileron D/R switch
- COM ELEV: Elevator D/R switch
- COM RUDD: Rudder D/R switch
- FLAP 2: Flap switch in the lower position
- FLAP 0: Flap switch in the upper position
- INDIVID: D/R activated by it's individual aileron, elevator and rudder switches



To Activate Dual Rate and Switch Select

Press and hold the **DOWN** and **SELECT** keys simultaneously to enter system mode.

Press the **UP** or **DOWN** key until **D/R SWITCH SEL** appears on the screen.

Press the **INCREASE** or **DECREASE** keys to select the desired switch(es) you wish to operate the D/R and Expo function.


Function Mode Functions

Dual Rate and Exponential

The Dual Rate and Exponential function allows two control rates to be programmed and selected with a switch. Dual rates and expos are available on the aileron, elevator and rudder channels. Changing the dual rate value not only affects the maximum control authority but also affects the overall sensitivity of control. A higher rate yields a higher overall sensitivity. The sensitivity around center can be tailored using the Exponential function to precisely adjust control feel.

Dual and Expo rates can be controlled by their respective dual rate switches (aileron, elevator and rudder) or by 1 common switch (COM AILE, COM ELEV, COM RUDD, FLAP0 or FLAP2). The choices for this are found on the D/R SWITCH SEL screen in the System Setup Mode for Airplanes.

Dual rate values are adjustable from 0–125%. The factory default settings for both the 0 and 1 switch positions are 100%. Exponential values are adjustable from -100% to +100%. Either switch position may be selected as the low or high rate by placing the switch in the desired position and adjusting the value accordingly.



To Adjust the Dual and Expo Rates

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In Function Mode, use the **UP** or **DOWN** keys to select the **D/R & EXP** screen.

Press the **INCREASE** or **DECREASE** key to select the desired channel (**AILE**, **ELEV** or **RUDD**).

Press the **SELECT** key to highlight the **D/R** or **EXPO** function.

Adjust the dual rate values for the selected switch position using the **INCREASE** or **DECREASE** keys.

The Dual Rate and Expo functions for aileron, elevator and rudder can be combined on a single switch conveniently allowing high or low rates to be selected via one switch (COM AILE, COM ELEV, COM RUDD, FLAP0 or FLAP2). The choices for this are found on the **D/R SWITCH SEL** screen in the System Setup Mode for Airplanes. (See Page 45)


Dual Rate and Exponential (continued)

The Exponential function allows two exponential rates to be programmed and selected with a switch. Exponential is available on the aileron, elevator and rudder channels. Changing the exponential value does not affect the maximum control authority but only affects control sensitivity. Exponential is normally used to reduce control sensitivity around neutral while still allowing high control authority at the extremes of throw. The sensitivity around center can be tailored using the Exponential function to precisely adjust control feel.

Exponential rates can be controlled by their respective rate switches (aileron, elevator and rudder), or combined on a single switch (COM AILE, COM ELEV, COM RUDD, FLAPO or FLAP2). The choices for this are found on the D/R SWITCH SEL screen in the System Setup Mode for Airplanes.

Exponential is available for the aileron, elevator and rudder channels. Expo values are adjustable from -100% (full negative expo), LIN (linear), and +100% (full positive expo). The factory default settings for both the 0 and 1 switch positions are LIN or 0%. Either switch position may be selected to give any desirable EXPO rate by placing the switch in the desired position and adjusting the value accordingly.

Note: A negative (-) Expo value will increase sensitivity around neutral, and a positive (+) Expo value will decrease sensitivity around neutral. Normally a positive value is used to desensitize control response around neutral.



To Adjust the Exponential

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In Function Mode, use the **UP** or **DOWN** keys to select the **DUAL RATE & EXPONENTIAL** screen.

Press the **INCREASE** or **DECREASE** key to select the desired channel (**AILE**, **ELEV** or **RUDD**).


Move the selected channel's dual rate switch to the desired position, 0 or 1.

Press the **SELECT** key until **EXP** is highlighted.

Adjust the Expo rate values for the selected switch position using the **INCREASE** or **DECREASE** keys.

Reverse Switch

The Reverse Switch function allows electronic means of reversing the servo's throw. Servo reversing is available for all seven channels.



To Access the Reverse Switch Mode

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In Function Mode, use the **UP** or **DOWN** key to select the Reverse screen.

Press the **SELECT** key to access the desired channel.

Press the **INCREASE** or **DECREASE** keys to reverse the servo direction for that selected channel. The channels available are:

- THRO: Throttle
- AILE: Aileron
- ELEV: Elevator
- RUDD: Rudder
- GEAR: Retractable Landing Gear
- FLAP: Flap
- AUX2: Auxiliary 2


Sub-Trim

The Sub-Trim function allows you to electronically adjust the centering of each servo. Sub trim is individually adjustable for all seven channels, with a range of + or - 125% (+ or - 30 degrees servo travel).

Caution: Do not use excessive sub-trim values as it is possible to overdrive the servo's maximum travel.

The channels available are:

- THRO: Throttle
- AILE: Aileron
- ELEV: Elevator
- RUDD: Rudder
- GEAR: Retractable Landing Gear
- FLAP: Flap
- AUX2: Auxiliary 2



To Access the Sub-Trim Function

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In Function Mode, use the **UP** or **DOWN** key to select the **SUB TRIM** screen.

Press the **SELECT** key to access the desired channel.


Press the **INCREASE** or **DECREASE** keys to adjust the sub-trim position for that selected channel.

Travel Adjust

The Travel Adjust function allows the precise end-point adjustments of all seven channels in each direction independently. The travel adjust range is from 0–150%.

Channel available for programming are:

- THRO: Throttle
- AILE: Aileron
- ELEV: Elevator
- RUDD: Rudder
- GEAR: Retractable Landing Gear
- FLAP: Flap
- AUX2: Auxiliary 2



To Access the Travel Adjust Function

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In Function Mode, use the **UP** or **DOWN** key to select the **TRAVEL ADJUST** screen.


Press the **SELECT** key to access the desired channel.

Move the selected channel's stick or switch in the desired direction that you wish to adjust.

Press the **INCREASE** or **DECREASE** keys to adjust the end-point position for that selected channel's direction.

Elevator-to-Flap Mix Function

When the Elevator-to-Flap Mixing System is active, and a value of flaps is input, the flaps will be deflected each time the elevator stick is used. The actual flap movement is independently adjustable for both up and down elevator. A commonly used application is up elevator/down flaps and down elevator/up flaps. When used in this manner, the aircraft pitches much more quickly than normal. The uppermost position of the Flap Mixing Switch or the Mix Switch can be used to activate the Elevator-to-Flap Mixing function. When you want to reverse the mixing directions, press the - key and change the mixing value from + to - (or - to +).



To Access the Elevator-to-Flap Mixing

In the Function Mode, use the **UP** or **DOWN** key to select the **ELEVATOR TO FLAP MIXING** function and access by pressing the **UP** and **DOWN** keys simultaneously.

Note: The flap mix switch, or the Mix switch, depending on which is selected, must be in the "ON" position to adjust values.

To adjust the rate value, with the switch on, move the elevator stick in the desired position up or down and press the **INCREASE** or **DECREASE** button to adjust the desired mix value.

To Select the Switch to Operate the Flap Mix


Press the **SELECT** key to highlight **SW**.

Press the **INCREASE** or **DECREASE** key to select the **MIX** or **FLAP0** switch position.

Aileron-to-Rudder Mixing

The Aileron-to-Rudder Mixing function is designed so that when input to the aileron stick is given, the rudder servo will also move, eliminating the need to coordinate these controls manually. This mixing program can be turned ON/OFF by a switch. The switches that can be selected are shown below, with their abbreviations as they appear on the screen and the corresponding switch positions. Mix values are adjustable from 0 to 125%. When adjusting the mix value, if an opposite mixing direction of the rudder servo is required, simply press the **INCREASE** or **DECREASE** key and change the mixing value from + to - or - to +. This will reverse the mixing direction of the rudder from its original direction.

- ON: Mixing Always ON
- MIX Switch ON/OFF Using Mixing Switch
- Flap 0 Switch ON/OFF Using Flap Mix Position 0
- Flap 2 Switch ON/OFF Using Flap Mix Position 2



To Access the Aileron-to-Rudder Mix Function

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In Function Mode, use the **UP** or **DOWN** key to select the **AILE-RUDD MIX** screen.

Press the **SELECT** key to highlight **RATE** or **SW** (switch).

To Adjust the Mix Value

With **RATE** highlighted, press the **INCREASE** or **DECREASE** keys to adjust the mix value.

Note: To reverse mix directions, a negative mix value is accessible.


To Assign a Switch

With **SW** highlighted, press the **INCREASE** or **DECREASE** keys to select the desired switch used to turn on/off the mix (Flap 0 or Mix).

Flap System

The purpose of the Flap System is to set the flap and elevator positions for landing and takeoff. This is accomplished by selecting values for the elevator and flaps to be activated when the Land Switch is engaged. Three flap and elevator positions are available. The landing system can also be activated by a preset position of the throttle stick. Refer to the Automatic Landing Attitude section for more information on how to select the preset throttle position.

Note: The Flap System is only operational when **SYSTEM** is selected under Flap in the Input Select screen. See page 41 for more detail.



Accessing and Utilizing the Flap System

Press the **UP** and **SELECT** keys simultaneously to enter the Function Mode.

Press either the **UP** or **DOWN** keys until **FLAP SYS** appears in the upper left portion of the LCD.


Press the **SELECT** key to position the cursor at the desired function (i.e., **ELEV**, **FLAP**, **SPOI**, **AUTO**).

Note: The flap system can only be accessed when **SYSTEM** is selected in the Input Select screen under flaps. See page 41 for more details.

Press the **UP** or **DOWN** keys to set the value for flap and elevator travel. The **UP** key adds up flap/elevator and the **DOWN** key adds down flap/elevator. The input is adjustable from 125% for flap and -200% for elevator.

Automatic Landing

When the Automatic Landing Function is active, the throttle stick will activate the landing system you have just set up. Any point of throttle stick travel can be set as the “auto-land” point. Once the throttle stick passes through this point and the LAND switch is in the MID, or land position, the landing system will be activated. Thus, the elevator and flaps would be activated. If the flap mixing switch is not in the LAND position, the throttle stick operation would have no effect on the landing system.



To Activate the Automatic Landing Feature

In the flap screen, press the **SELECT** key until **AUTO** is highlighted.

Press either the **INCREASE** or **DECREASE** key to activate the **AUTOMATIC LANDING SYSTEM**.


To change this value, press the **INCREASE** or **DECREASE** key to adjust the value (0% = low stick while 100% = full stick).

To clear the auto land point, press **CLEAR** and the display will return to **INH**.

Differential Aileron Mixing

Note: Only available when Flaperon or Elevon is activated (see Wing Type Page 39).

The Differential Aileron function allows precise electronic adjustments of the up vs. down aileron travel of both ailerons. Aileron differential is used to reduce unwanted yaw characteristics during roll inputs. In order to access the Differential Function, flaperon or elevon wing mixing must be selected and two servos must be used to operate the ailerons.



To Access the Differential Aileron Mixing Function

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In Function Mode, use the **UP** or **DOWN** key to select the **DIFFERENTIAL** screen.

Press the **INCREASE** or **DECREASE** keys to adjust the Differential value.


Note: Increasing the value will reduce the amount of down travel in each aileron.

If differential is working in reverse, the aileron servos are plugged into the wrong (opposite) channels. The right aileron should be plugged into the aileron channel, while the left aileron should be plugged into the flap channel.

Programmable Mixing 1–6

The DX7 offers six (6) programmable mixes that allow stick or switch inputs to control the output of two or more servos. This function allows mixing any one channel to any other channel, or the ability to mix a channel to itself. The mix can remain ON at all times, or it can be switched OFF in flight, using a number of different switches. Mix values are adjustable from 0 to 125%. Each channel is identified by a four-character name (i.e., Aileron - AILE, Elevator - ELEV, etc.). The channel appearing first is the master channel. The second channel is the slave channel. For example, AILE - RUDD would indicate aileron-to-rudder mixing. Each time the aileron stick is moved, the aileron will deflect, and the rudder will automatically move in the direction and to the position based on the value input in the programmable mix screen. Mixing is proportional, so small inputs of the master channel will produce small outputs of the slave channel. Each programmable mix has a mixing offset. The purpose of the mixing offset is to redefine the neutral position of the slave channel.

Note: Programmable mix 5 and 6 have a built-in trim include function. If programmable mix 5 or 6 is selected, and a master channel is selected that has a trim lever (ie. aileron, elevator rudder or throttle), the trim will operate both the master and the slave channel.



Programmable Mixing 1–6 (continued)

Assigning Channels


Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In Function Mode, use the **UP** or **DOWN** keys to select the desired **PROG. MIX** screen (1–6).

Press the **INCREASE** or **DECREASE** keys to select the desired master channel.

Press the **SELECT** key to highlight the slave channel.

Press the **INCREASE** or **DECREASE** keys to select the desired slave channel.



Assigning Mixing Values

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In Function Mode, use the **UP** or **DOWN** keys to select the desired **PROG. MIX** screen (1–6).

Press the **SELECT** key to highlight **RATE**.


Using the stick or switch that is assigned to the master channel, move that stick or switch in the desired direction that you wish to adjust the mix value.

Press the **INCREASE** or **DECREASE** keys to adjust the mix value. values are adjustable from -125% to +125%.

Note: If a switch is assigned to the mix, that switch must be turned on to allow mixing values to be changed.

Moving the stick or switch in the opposite direction will allow the mix value to be adjusted in the opposite direction.

Programmable Mixing 1–6 (continued)



Assigning an Offset

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In Function Mode, use the **UP** or **DOWN** keys to select the desired **PROG. MIX** screen (1–6).

Press the **SELECT** key to highlight **OFFSET**.

To establish the offset position, use the **INCREASE** or **DECREASE** keys to change the value to the desired point. The stored offset value will appear onscreen.

To change the offset value, simply use the **INCREASE** or **DECREASE** keys to change the value. Pressing the **CLEAR** button will reset the offset to 0.

Assigning a Switch

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In Function Mode, use the **UP** or **DOWN** keys to select the desired **PROG. MIX** screen (1–6).

Press the **SELECT** key to highlight **SW**.

Use the **INCREASE** or **DECREASE** keys to select the desired switch to turn on/off the mix.

- ON: Mixing Always On
- MIX: Mixing Switch Toward Self
- Flap 0: Flap Switch in Flap 0 Position
- Flap 2: Flap Switch in Flap 2 Position
- Gear: Gear Switch

Timer

The DX7 features an onscreen timer with three programming options:

INH:

Inhibit- In this mode the timer is turned off.

Down-T:

Down Timer- The countdown timer allows a preset time in ten-second intervals up to 59 minutes and 50 seconds to be programmed, and when that time expires, a beeper will sound for 10 seconds.

STOP-W:

Stopwatch- The stopwatch function is a simple count-up timer that that displays minutes and seconds up to 59 minutes and 59 seconds.


When the **DOWN-T** or **STOP-W** function is selected, the timer will be displayed on the main screen. The following buttons are used in conjunction to operate the timer function:

INCREASE or **DECREASE** keys:


Used to start, stop and restart the timer.

CLEAR key:

Used to reset the timer to the preset time (Down-T) or to reset the stopwatch timer to 0:00.



Timer (continued)



Press the **DOWN** and **SELECT** keys simultaneously to access the system mode.


In System Mode use the **UP** or **DOWN** key to select the **TIMER** screen.

Press the **SELECT** key to select **STOP-W**, **DOWN-T** or **INH**.

With **DOWN-T** selected press the **INCREASE** or **DECREASE** key to change the preprogrammed time.


Servo Monitor

The servo monitor screen serves as a useful tool when programming your radio. It displays servo positions and is useful in checking different programming functions.




Helicopter Programming Guide

Transmitter Control Identification and Location



General Information



Key Input and Display Functions

- The **UP** and **DOWN** keys are used to select the programming function.
- The **SELECT** key is used to select the channel or feature that you wish to program.
- The **INCREASE** or **DECREASE** keys are used to change the values of the selected programming feature.

The DX7 features two programming modes: System Setup Mode and Function Mode, which are described in the next sections.

Warning Screen for Throttle Hold/Stunt Mode

When the DX7 is operated in the helicopter mode, there is a warning system that is employed to avoid hot starts (accidental high throttle startups) when the power switch is initially turned ON. If the flight mode switch or throttle hold is on, an alarm will sound and a warning message will be displayed on the LCD. When all switches are returned to the normal condition, the display will return to normal.

Note: If the Throttle Hold function is not activated prior the power switch being turned ON, no alarm will sound. Below is the display example of WARNING CONDITION when the power switch is ON.




Gyro Connections

Note: The Gyro Gain channel can be selected to operate on Channel 5 (Gear) or Channel 7 (AUX2). See input Select on Page 73 for detail on selecting the gain channel.

System Setup Mode

Includes programming functions that are normally used during setup. System Setup programming functions include:

Model Select (Page 67)	<pre>[MODEL SELECT] ▶SELECT MODEL 1 T-REX HELI DSM</pre>	<pre>[SWASH TYPE] 1 SERVO NORM</pre>	Swash Type (Page 75)
Model Name (Page 68)	<pre>[MODEL NAME] MODEL 1 HELI DSM <T-REX450> ↑</pre>	<pre>[INPUT SELECT] →AUX2 GEAR GYRO INH</pre>	Input Select (Page 73)
Type Select (Page 69)	<pre>[TYPE SELECT] MODEL 1 ▶HELI  ACRO </pre>	<pre>[THRO RECOVERY] INH</pre>	Throttle Recovery (Page 72)
Model Reset (Page 70)	<pre>[MODEL RESET] MODEL 1 HELI DSM ▶DATA RESET INTEG-T 0:00:34</pre>	<pre>[TRAINER] →NORMAL SW=L-ROCKER</pre>	Trainer (Page 71)



To Enter the System Setup Mode


- With the power switch off, press and hold the **DOWN** and **SELECT** keys simultaneously.
- Turn on the power switch.
- The system will display the last system setup screen that was used.

To Exit the System Setup Mode

- Press the **DOWN** and **SELECT** keys simultaneously.
- The main menu will be displayed
- Or turn the transmitter off to exit the System Setup Mode.

Model Select/Copy


The DX7 features a memory function that stores the programmed data for up to 20 models. Any combination of up to 20 airplanes and/or helicopters can be stored in memory. A model name feature with up to eight characters allows each model to be easily identified.



To Enter the Model Select Function

Press the **DOWN** and **SELECT** keys simultaneously and turn the power switch ON to access the System Setup Mode. Press the **INCREASE** or **DECREASE** key until the **MODEL SELECT** screen appears.

Press the **INCREASE** or **DECREASE** key to select the desired model memory.




To Enter the Copy Function

- Press the **DOWN** and **SELECT** keys simultaneously and turn the power switch ON to access the System Setup Mode.
- Press the **UP** or **DOWN** key until **MODEL SELECT** appears on screen.
- Press the **SELECT** button to enter the **COPY** screen.
- Press the **INCREASE** or **DECREASE** keys to select to model that you wish to copy the model to.
- Press the **CLEAR** key to copy the model to the selected model memory.

Note: Be aware that the model that you copy to will have its memory replaced with the new model and the programming information for that model will be erased.

Model Name

The Model Name function is used to input and assign the model's name to a specific memory, allowing easy identification of each model's program. Each model's name is displayed on the main screen when that model is selected. Up to eight characters that include numbers and letters are available.



To Enter the Model Name Function

Press the **DOWN** and **SELECT** keys simultaneously, then turn on the transmitter.

Press the **INCREASE** or **DECREASE** key until the **MODEL NAME** screen appears.

Press the **SELECT** Key to move the cursor to the desired character's position.

Press the **INCREASE** or **DECREASE** key to select the desired character.

Model Match

The DX7 features patented Model Match™ technology that prevents operating a model using the wrong memory. This feature can prevent stripped servo gears, broken linkages and even a crash due to trying to operate/ fly a model using the wrong memory.


How Model Match Works

Each individual model memory has its own embedded code that is transferred to the receiver during binding. The receiver actually learns the code for the specific model memory that has been selected during binding and, when bound, will only operate when that model memory is selected. If a different (non-matching) model memory is selected, the receiver simply won't connect. This feature prevents trying to operate/ fly a model using the wrong model memory. The receiver can be re-programmed to operate with any other model memory by simply re-binding with the transmitter programmed to the desired model memory.

Note: If the receiver is turned on and the matching model memory is not selected the system will not connect. Either select the matching model memory or rebind the receiver in the current model memory to resume operation.

Type Select Function


The DX7 features two programming types: Airplane and Helicopter. The DX7 can memorize data for up to 20 models individually.



To Enter the Type Select Mode

Press the **DOWN** and **SELECT** keys simultaneously, then turn on the transmitter.

Press the **UP** key until the **TYPE SELECT** function appears on screen.




To Select a Model Type

Press the **INCREASE** or **DECREASE** key to toggle between the heli or acro model types.

To accept the new model type press the **CLEAR** key. All settings will be set to the factory defaults.


Model Reset/Integrated Timer

The Model Reset function resets all programming functions to their default settings. This screen also allows you to reset the integrated timer function to zero.



To Reset a Model

- Press the **DOWN** and **SELECT** keys simultaneously, then turn on the transmitter.
- Press the **UP** key until **MODEL RESET** appears on screen.
- Press the **SELECT** key until **DATA RESET** is highlighted.
- Pressing the **CLEAR** key will reset the model memory to factory default settings.



To Reset the Integrated Timer

- Press the **DOWN** and **SELECT** keys simultaneously, then turn on the transmitter.
- Press the **UP** key until the **MODEL RESET** function appears on screen.
- Press the **SELECT** key until **INTEG-T** is highlighted.
- Pressing the **CLEAR** key will reset the **INTEG-T** to factory zero.

Trainer

The DX7 offers a programmable Trainer function that allows the transmitter to operate in three different Trainer modes. The left or right rocker can be programmed as the trainer switch.

NORMAL:


The transmitter can be used as a master or slave, but the slave transmitter must have the same programming (i.e. reverse, travel adjust, dual rates, mixes sub trims, etc.) as the master.

P-LINK:

In Pilot Link the master transmitter maintains control of all secondary functions (i.e. dual rate, expo, gear, flaps, etc.) and only the primary stick controls (aileron, elevator, rudder and throttle) are transferred to the slave transmitter when the trainer switch is pressed.

SLAVE/P-LINK:

In the Slave mode, the DX7 is used as a slave radio in conjunction with a Spektrum® radio that is used as the master that is in P-LINK mode; there is no need to match the slave's programming to the master transmitter's programming in this mode.



To Enter the Trainer Mode

Press the **DOWN** and **SELECT** keys simultaneously, then turn on the transmitter.

Press the **UP** key until **TRAINER** function appears on screen.

Press the **INCREASE** or **DECREASE** key to select the desired Trainer type: INH, Normal, P-Link or Slave/P-Link. Also note that the trainer switch can be located on the right or left rocker switch. Use the select key to highlight SW:R then press the increase or decrease key to select the right (R) or left (L) rocker.

Throttle Recovery

The DX7 has a unique throttle trim recovery feature. Throttle Recovery stores the last known throttle trim position before the trim is moved to the full down (closed) position. That stored position is then recalled by moving the throttle trim up (open) one notch. This makes shutting off the engine and restarting it with the correct trim position easy. Throttle Recovery must be activated for each model.



To Activate the Throttle Recovery Function


Press the **DOWN** and **SELECT** keys simultaneously, then turn on the transmitter.

Press the **UP** key until **THRO RECOVERY** appears on screen.

Press the **INCREASE** or **DECREASE** key to turn on/off the Throttle Recovery function.

Input Select

The Input Select function is used to select the switch input for the gyro gain and the channel that will operate the gyro gain.



To Select the Function for the AUX2 Channel

Press the **DOWN** and **SELECT** keys simultaneously, then turn on the transmitter.

Press the **UP** or **DOWN** key until the **INPUT SELECT** function appears on screen.

Press the **SELECT** key until **AUX2** is highlighted.

Press the **INCREASE** or **DECREASE** key to select the desired function.

The Auxiliary 2 channel options are:

INH:

Inhibit is selected if the gyro function will not be used on the Aux 2 channel.

F.MODE:

In this mode, the AUX2 channel is controlled by the flight mode switch and three positions are available. Sub trim and travel adjust is used to set the center and end points for each switch position.


AUX2:

The Auxiliary 2 switch controls the AUX2 Channel.

GYRO:

The gyro mode is selected if you want to use the Gyro Sensing (see page 91) for more detail. Selecting GYRO under AUX2 assigns the gyro sensing program to operate use the AUX2 channel. In this case the gyro gain must be plugged into the AUX2 (Channel 7) channel.

Input Select (continued)



To Select the Function for the Gear Channel

Press the **DOWN** and **SELECT** keys simultaneously, then turn on the transmitter.

Press the **UP** or **DOWN** key until **INPUT SELECT** appears on screen.

Press the **SELECT** key until **GEAR** is highlighted.

Press the **INCREASE** or **DECREASE** key to select the desired function.

The gear channel options are:

INH:

Inhibit is selected if the gyro function will not be used on the gear channel. Selecting inhibit turns off the gear channel, allowing it to be used as a slave channel for mixing.

GEAR:

Gear is selected if the gyro gain or retractable gear position is to be selected using the gear switch.

GYRO:

Gyro is selected under gear if you wish to have the Gyro Sensing (Page 91) operate using the gear channel.

AUX2:



The Auxiliary 2 switch is used to activate the gear channel.

Swash Type

The Swashplate Mixing function enables the DX7 system to operate the following swashplate types:

The Swashplates are:

- 1 Servo: Non-CCPM, standard mixing type helicopter
- 2 Servo/180° CCPM
- 3 Servo/120° CCPM (most popular)
- 3 Servo/90° CCPM



Accessing the Swashplate Types

While pressing the **DOWN** and **SELECT** keys, turn the transmitter on to enter the System Mode.








Press either the **UP** or **DOWN** key until **SWASH TYPE** is displayed in the LCD.

Press the **INCREASE** or **DECREASE** keys to change the swashplate type.


Pressing the **CLEAR** key will reset the swashplate type to the **NORMAL** position.

Function Mode Flowchart

Includes programming functions that are more frequently used. Function Mode programming functions include:

Dual Rate & Exponential (Page 79)		
Auto Dual Rate Expo (Page 81)		Servo Monitor (Page 97)
Reverse (Page 82)		Timer (Page 95)
Sub Trim (Page 83)		Programmable Mix (1 though 3) (Page 92)
Travel Adjust (Page 84)		Gyro Sensing (Only available when AUX2 or GEAR is assigned as Gyro Function) (Page 91)
Swashplate Mix (Only available when CCPM Mix is active) (Page 85)		Revo Mix (Page 90)
Throttle Hold (Page 86)		Pitch Curve Hold (only available when HOLD is activated) (Page 89)
Throttle Curve Normal (Page 87)		Pitch ST-2 (Page 89)
Throttle Curve ST-1 (Page 87)		Pitch Curve ST-1 (Page 89)
Throttle Curve ST-2 (Page 87)		Pitch Curve Normal (Page 89)

Function Mode (continued)



To Enter the Function Mode

- Turn the transmitter on.
- From the main screen press the **DOWN** and **SELECT** keys simultaneously.
- The system is now in Function Mode and will display the last screen that was used in Function Mode.

To Exit the Function Mode

- Press the **DOWN** and **SELECT** keys simultaneously. The system will return to the main screen.



List Modes

The list mode screens display all the functions onscreen, allowing the access of any function without having to scroll through each screen. Note that there are two list modes: a System Setup list mode that displays all the system setup functions and a Function list mode that displays all the system programming functions.

To enter the System Setup List Mode, with the system on and in any System Setup function, press the **UP** and **SELECT** keys simultaneously.

To enter the Function List mode, with the system on and in any function mode screen, press the **UP** and **SELECT** keys simultaneously.

In either List Mode, pressing the **UP** and **DOWN** keys will move the cursor to the desired function. Then pressing the **DOWN** and **SELECT** key simultaneously will access the selected function.




Function Mode Functions

Dual Rate and Exponential

The Dual Rate and Exponential function allows two control rates to be programmed and selected with a switch. Dual rates and exponentials are available on the aileron, elevator and rudder channels. Changing the dual rate value not only affects the maximum control authority but also affects the overall sensitivity of control. A higher rate yields a higher overall sensitivity. The sensitivity around center can be tailored using the Exponential function to precisely adjust control feel.

Dual rates can be controlled by their respective dual rate switches (aileron, elevator and rudder). An auto dual rate function is available that allows to automatic selection of the desired rates via the three-position flight-mode switch.

Exponential values are adjustable from -100% to +100%. The factory default settings for both the 0 and 1 switch positions are 100%. Either switch position may be selected as the low or high rate by placing the switch in the desired position and adjusting the value accordingly.



To Adjust the Dual Rate

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In Function Mode, use the **UP** or **DOWN** keys to select the **D/R & EXP** screen.

Press the **INCREASE** or **DECREASE** key to select the desired channel (**AILE**, **ELEV** or **RUDD**).

Press the **SELECT** key to highlight the **D/R** or **EXPO** function.

Adjust the dual rate values for the selected switch position using the **INCREASE** or **DECREASE** keys.


The Dual Rate and Expo functions for aileron, elevator and rudder can be combined on the flight mode auto dual rate/expo conveniently allowing high or low rates to be selected via the flight mode switch. See Page 81 for more details.

Dual Rate and Exponential (continued)

The Exponential function allows two exponential rates to be programmed and selected with a switch. Exponential is available on the aileron, elevator and rudder channels. Changing the exponential value does not affect the maximum control authority but only affects control sensitivity. Exponential is normally used to reduce control sensitivity around neutral while still allowing high control authority at the extremes of throw. The sensitivity around center can be tailored using the Exponential function to precisely adjust control feel.

Exponential rates can be controlled by their respective rate switches (aileron, elevator and rudder), or combined on a flight mode switch. Exponential is available for the aileron, elevator and rudder channels. Expo values are adjustable from -100% (full negative expo), LIN (linear), and +100% (full positive expo). The factory default settings for both the 0 and 1 switch positions are LIN or 0%. Either switch position may be selected to give any desirable EXPO rate by placing the switch in the desired position and adjusting the value accordingly.

Note: A negative (-) Expo value will increase sensitivity around neutral, and a positive (+) Expo value will decrease sensitivity around neutral. Normally a positive value is used to desensitize control response around neutral.



To Adjust the Exponential

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In Function Mode, use the **UP** or **DOWN** keys to select the **DUAL RATE AND EXPONENTIAL** screen.

Press the **INCREASE** or **DECREASE** key to select the desired channel (**AILE**, **ELEV** or **RUDD**).


Move the selected channel's dual rate switch to the desired position, 0 or 1.

Press the **SELECT** key until **EXP** is highlighted.

Adjust the Expo rate values for the selected switch position using the **INCREASE** or **DECREASE** keys.

Auto Dual Rate EXP

The Auto Dual Rate and Expo function allows Expo and Dual Rate values (aileron, elevator and rudder) to be automatically selected in each flight mode (Normal, ST1, ST2, and Hold.) When an auto dual rate flight mode is inhibited, the dual rate is defaulted to the correlating switch and dual rate switch positions.



To Adjust the Auto Dual Rate

Press the **DOWN** and **SELECT** key simultaneously to access the Function Mode.

Press the **UP** or **DOWN** key until the **AUTO D/R EXP** screen appears on screen.


Use the select key to select **NORMAL**, **ST1** **ST2** or **HOLD FLIGHT** mode.

When selected, press the **INCREASE** or **DECREASE** key to select **DUAL RATE**, **P-1**, **P-2** or **INHIBIT**.

Note: The actual dual rate values are set in the Dual Rate and Expo screen. See Page 79.

Reverse Switch

The Reverse Switch function allows electronic means of reversing the servo's throw. Servo reversing is available for all seven channels.



Accessing the Reverse Switch Function

Press the **SELECT** key to access the desired channel.

Press the **INCREASE** or **DECREASE** keys to reverse the servo direction for that selected channel.

- THRO: Throttle
- AILE: Aileron
- ELEV: Elevator
- RUDD: Rudder
- GEAR: Gyro Gain
- PIT: Pitch (AUX1) Gyro Gain

Sub Trim


The Sub-Trim function allows you to electronically adjust the centering of each servo. Sub trim is individually adjustable for all seven channels, with a range of + or - 125% (+ or - 30 degrees servo travel).

Caution: Do not use excessive sub-trim values as it is possible to overdrive the servo's maximum travel.

Sub-trim value (max ± 125).

The channels available are:

- THRO: Throttle
- AILE: Aileron
- ELEV: Elevator
- RUDD: Rudder
- GEAR: Retractable Landing Gear
- PIT.: Pitch
- AUX2: Auxiliary 2



To Access the Sub-Trim Function

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In Function Mode, use the **UP** or **DOWN** key to select the **SUB TRIM** screen.

Press the **SELECT** key to access the desired channel.


Press the **INCREASE** or **DECREASE** keys to adjust the sub-trim position for that selected channel.

Travel Adjust

The Travel Adjust function allows the precise end point adjustments of all seven channels in each direction independently. The travel adjust range is from 0–150%.

Channel available for programming are:

- THRO: Throttle
- AILE: Aileron
- ELEV: Elevator
- RUDD: Rudder
- GEAR: Retractable Landing Gear
- PIT.: Pitch
- AUX2: Auxiliary 2



To Access the Travel Adjust Function

Press the **SELECT** key to access the desired channel.



Move the selected channel's Stick or switch in the desired direction that you wish to adjust.

Press the **INCREASE** or **DECREASE** keys to adjust the sub-trim position for that selected channel's direction.

Swashplate Mixing

The Swashplate Mix screen is only displayed when a CCPM swashplate mix is activated. (See Page 75 for Swashplate Type to enable Swashplate Mix.) Swashplate Mix adjusts the amount, and direction of travel, for the aileron, elevator and pitch functions. For example, if more aileron travel is desired, increasing the aileron swashplate mix value will increase the overall travel of the servos necessary to achieve greater aileron throw.

Note: Negative values are available which will reverse the direction of that function.



Accessing the Swashplate Mix Function

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In function mode, press the **UP** or **DOWN** key to select the **SWASH MIX** screen.


Press the **SELECT** key to access the desired function (**AILERON**, **ELEVATOR**, **PITCH** or **EXPO**).

Press the **INCREASE** or **DECREASE** key to change the selected swashplate mix value.

Note: Selecting a negative value will reverse the direction of the function.

Throttle Hold

The Throttle Hold function is used to practice autorotation and is often used as a safety switch for electric helicopters, holding the throttle in the off position. When the throttle hold switch is activated, the throttle hold function holds the throttle servo/ ESC in a specific position (normally low or off throttle) while all other servos function normally. The throttle hold switch is also selectable. Switch selection options include rudd D/R, gear, AUX2, aileron D/R or elevator D/R.



To Access the Throttle Hold Function

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In Function Mode, use the **UP** or **DOWN** key to select the **THRO HOLD** screen.

Press the **INCREASE** or **DECREASE** key to activate the throttle hold function.

When activated, press the **INCREASE** or **DECREASE** key to change the throttle hold value.

To Access the Throttle Hold Switch Function

Press the **SELECT** key to highlight switch.

Press the **INCREASE** or **DECREASE** key to select the desired switch.

Throttle Curve


The DX7 offers three (3) separate throttle curves with five (5) adjustable points per curve. This function allows you to adjust the throttle curve to optimize engine rpm at a particular pitch setting. Once the throttle curves are established, each can be activated in flight using the 3-position flight mode switch. The flight mode switch offers three (3) selectable curves: N=Normal, 1=Stunt 1, 2=Stunt 2.

The N, or Normal, position should be used for starting the engine and hovering. Positions 1 and 2, or Stunt 1 and Stunt 2, should be used for aerobatic maneuvers and forward flight.

Note: The throttle trim and hovering throttle lever are only operable when the flight mode switch is in the Normal position. Thus, in the 1 or 2 positions, these two functions have no effect.

Each of the five (5) positions of the throttle curve are independently adjustable from 0–100%. These five (5) positions correspond to the position of the throttle stick.

The transmitter is factory preset to the throttle curve as indicated by the solid line in the figure below. Individual points can be activated and increased/decreased to suit your specific needs.



To Access the Throttle Curve Function

Press the **DOWN** and **SELECT** keys simultaneously to access the System Mode.

In System Mode, use the **UP** or **DOWN** keys to select the **THRO CURVE NORM** screen.

Press the **SELECT** button to access pitch points L (Low), **1**, **2**, **3**, or **H** (High) or **EXPO**.

Press the **INCREASE** or **DECREASE** keys to change the selected pitch value or expo on/off.

Throttle Curve (continued)

Throttle Trim Setting

The throttle trim lever is only active when the flight mode switch is in the normal position. The throttle trim is used to increase or decrease the engine rpm to achieve a reliable idle when in the Normal Mode. The throttle trim lever has no effect in flight modes 1 or 2 (Stunt 1 or Stunt 2), or throttle hold.

Hovering Throttle Rocker Setting

The hovering throttle rocker increases or decreases the engine throttle position for the center point only (point #2) of the throttle curve. Use of the hovering throttle rocker shifts the middle curve upward or downward. Therefore, operation of the hovering throttle rocker does not cause any change to the high point and low point of the throttle curve but only affects the hovering rpm. The hovering throttle rocker only affects the throttle curve in normal mode and has no effect on the curve in Stunt 1 or Stunt 2.

Exponential Throttle Curve Function

With the DX7 system, individual throttle curves are selectable to be either straight (linear) or curved (exponential). To select an exponential curve, press the select key until EXP OFF appears on the throttle curve screen. Next press either the increase or decrease key to activate the exponential feature (an “on” will replace the “off” on the screen). With the exponential function ON, you will notice that any “sharp” angles of the throttle curve will become more “rounded” or “smooth,” creating a smooth throttle servo movement during the entire throttle curve range.

Idle Up

Normally, flight mode 1 and 2 are used to increase engine rpm below half stick for forward flight and aerobatic maneuvers (idle up), and at this time any other trims are not active as the throttle will only operate/follow the current throttle curve values.

Stunt 1 and Stunt 2

Note: Throttle curves are adjusted independent of the normal throttle curve. Simply select the desired throttle curve by using the up or down keys.


Pitch Curve

Adjustment of the pitch curve is very similar to the throttle curve adjustment described in the preceding section. A thorough understanding of the throttle curve section will make pitch curve adjustment easier to understand.

The DX7 offers four (4) independent pitch curves: Normal, Stunt 1, Stunt 2 and Hold. Each pitch curve contains five (5) adjustable points — L, 1, 2, 3, and H.

Note: When setting pitch curve for throttle hold, it is necessary for the throttle hold to be active — if this function is inhibited, the throttle hold pitch curve will not be visible on the screen.

In the Function Mode, use the **UP** and **DOWN** keys to select **PITCH CURVE**.



To Access the Pitch Curve Function

Press the **DOWN** and **SELECT** keys simultaneously to access the System Mode.

In System Mode, use the **UP** or **DOWN** keys to select the **PITCH CURVE NORM** screen.

Press the **SELECT** button to access pitch points L (Low), **1**, **2**, **3**, or **H** (High) or **EXPO**.

Press the **INCREASE** or **DECREASE** keys to change the selected pitch value or expo on/off.

Hovering Pitch Rocker

The hovering pitch rocker operates in the same manner as the hovering throttle rocker. It is operable while the flight mode is in the N, or Normal, position, and its function is to shift the center point (#2) of the curve either upward or downward to adjust pitch at the hover position.


Revolution Mixing (only used with non-heading hold gyros)

The Revolution Mixing Function mixes tail rotor input with the Throttle/Collective function to counteract torque from the main rotor blades. When set up correctly, the helicopter should climb and descend without a tendency to yaw in either direction. Because torque reaction varies with different power settings, it is necessary to vary the tail rotor pitch at the same time. The DX7 offers two (2) separate revolution mixing programs with independent up and down mixing for each—one for flight mode position N, and the other for Stunt 1 and Stunt 2 positions. The U, or Up, mixing adjusts the tail rotor compensation for the mid to high throttle/stick setting, and the D, or Down, mixing adjusts the tail rotor compensation for the mid to low throttle/stick setting.

In the Function Mode, use the **UP** or **DOWN** keys to select Revolution Mixing screen.

Setting Up Revolution Mixing

First, adjust the helicopter so that it will hover in a neutral position with the tail rotor trim at center. Next, establish the helicopter into a stable hover; then steadily increase the throttle to initiate a stable climb. The body of the helicopter will move in the opposite direction to the main rotor rotation. Increase the U, or Up, setting until the helicopter will climb with no tendency to turn or rotate. At a safe altitude, close the throttle and the helicopter will descend with the body turning in the same direction as the main rotor. Increase the D, or Down, mix until the helicopter descends with no tendency to turn or rotate. When attempting this procedure, throttle stick movements should be slow, and the initial acceleration and deceleration swings should be overlooked.



To Access Revolution Mixing


Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

Press the **SELECT** key to select the desired function.

Press the **INCREASE** or **DECREASE** key to change the value or function.

Gyro Sensing

The DX7 offers two different types of Gyro Sensitivity Adjustments — manual or automatic. This feature gives the user the choice of selecting gyro sensitivity manually through the rudder dual rate switch or automatically through the flight mode switch.



To Access the Gyro Sensing Function

In function mode, press the **UP** or **DOWN** key until **GYRO SENS** screen appears on the screen.

Use the **SELECT** key to highlight the desired **RATE** or **FLIGHT MODE**.

Press the **INCREASE** or **DECREASE** key to change the rate value or the select position 0 or 1 for each flight mode.

Note: In order to access the Gyro Sensing function, it is necessary to select Gyro in the Input Select screen and assign it to AUX2 or the gear channel. See Page 73 for more details.

Manual Gyro Sensitivity Adjustment

Manual Gyro Sensitivity Adjustment allows the pilot to select from two different gyro sensitivities during all flight conditions. This function is activated in conjunction with the rudder dual rate switch.


Automatic Gyro Sensitivity Adjustment

The Automatic Gyro Sensitivity Adjustment feature allows the pilot to automatically alter the sensitivity of the gyro from either of two pre-determined settings through the use of the flight mode switch. As different flight modes are selected (Normal, 1, 2, Hold), the Gyro's sensitivity rate will switch to the pre-determined compensation rate for each particular flight mode in use.

Programmable Mixing 1–3

In helicopter mode the DX7 offers three (3) programmable mixes that allow stick or switch inputs to control the output of two or more servos. This function allows mixing any one channel to any other channel or the ability to mix a channel to itself. The mix can remain ON at all times, or be switched OFF in flight using a number of different switches. (Refer to chart below.) Mix values are adjustable from 0 to 125%. Each channel is identified by a four-character name (i.e., Aileron - AILE, Elevator - ELEV, etc.). The channel appearing first is the master channel. The second channel is the slave channel. For example, AILE - ELEV would indicate aileron-to-elevator mixing. Each time the aileron stick is moved, the elevator will deflect, and the elevator will automatically move in the direction and to the position based on the value input in the programmable mix screen. Mixing is proportional, so small inputs of the master channel will produce small outputs of the slave channel. Each programmable mix has a mixing offset. The purpose of the mixing offset is to redefine the neutral position of the slave channel.

- ON: Mixing always on
- F-NR: Flight mode normal
- F-S12: Stunt modes 1 and 2
- F-S2: Stunt mode 2
- HOLD: Throttle hole toward self
- GEAR: Gear channel toward self



Assigning Channels

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.


In Function Mode, use the **UP** or **DOWN** keys to select the desired **PROG. MIX** screen (1–3). Press the **INCREASE** or **DECREASE** button to access the Programmable Mix function.

Press the **INCREASE** or **DECREASE** keys to select the desired master channel.

Press the **SELECT** key to highlight the slave channel.

Press the **INCREASE** or **DECREASE** keys to select the desired slave channel.

Programmable Mixing 1–3 (continued)



Assigning Mixing Values

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In Function Mode, use the **UP** or **DOWN** keys to select the desired **PROG. MIX** screen (1–3).

Press the **SELECT** key to highlight **RATE**.


Using the stick or switch that is assigned to the master channel, move that stick or switch in the desired direction that you wish to adjust the mix value.

Press the **INCREASE** or **DECREASE** keys to adjust the mix value.

Note: If a switch is assigned to the mix, that switch must be turned on to allow mixing values to be changed.

Moving the stick or switch in the opposite direction will allow the mix value to be adjusted in the opposite direction.

Programmable Mixing 1–3 (continued)



Assigning an Offset

Press the **DOWN** and **SELECT** keys simultaneously to access the Function Mode.

In Function Mode, use the **UP** or **DOWN** keys to select the desired **PROG. MIX** screen (1–3).

Press the **SELECT** key to highlight **OFFSET**.

Move the master channel's stick to the desired offset position and press the **CLEAR** key to store that offset value. The stored offset value will appear onscreen.

To change the offset value, simply move the master channel's stick to the desired position and press the **CLEAR** button.

Timer

The DX7 features an onscreen timer with three programming options:

INH:

Inhibit- In this mode the timer is turned off.

DOWN-T:

Down Timer- The countdown timer allows a preset time in ten-second intervals up to 59 minutes and 50 seconds to be programmed and when that time expires a beeper will sound for 10 seconds.

STOP-W:

Stopwatch- The stopwatch function is a simple count-up timer that that displays minutes and seconds up to 59 minutes and 59 seconds.


When the **DOWN-T** or **STOP-W** function is selected, the timer will be displayed on the main screen. The following buttons are used in conjunction to operate the timer function:

INCREASE or **DECREASE** keys:


Used to start, stop and restart the timer.

CLEAR key:

Used to reset the timer to the preset time (Down-T) or to reset the stopwatch timer to 0:00.



Timer (continued)



To Access the Timer Function

Press the **DOWN** and **SELECT** keys simultaneously to access the system mode.


In System Mode use the **UP** or **DOWN** key to select the **TIMER** screen.

Press the **SELECT** key to select **STOP-W**, **DOWN-T** or **INH**.

With **DOWN-T** selected press the **INCREASE** or **DECREASE** key to change the preprogrammed time.

Servo Monitor

The servo monitor screen serves as a useful tool when programming your radio. It displays servo movement and direction when different programming functions, sticks and/or switches are moved.



General Information

FCC Information

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Caution: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This product contains a radio transmitter with wireless technology which has been tested and found to be compliant with the applicable regulations governing a radio transmitter in the 2.400GHz to 2.4835GHz frequency range.

The associated regulatory agencies of the following countries recognize the noted certifications for this product as authorized for sale and use:

Instructions for Disposal of WEEE by Users in the European Union

This product must not be disposed of with other waste. Instead, it is the user's responsibility to dispose of their waste equipment by handing it over to a designated collection point for the recycling of waste electrical and electronic equipment. The separate collection and recycling of your waste equipment at the time of disposal will help to conserve natural resources and ensure that it is recycled in a manner that protects human health and the environment. For more information about where you can drop off your waste equipment for recycling, please contact your local city office, your household waste disposal service or where you purchased the product.

USA	Canada	Belgium
Denmark	France	Finland
Germany	Italy	Netherlands
Spain	Sweden	UK



Servo Precautions

- Do not lubricate servo gears or motors.
- Do not overload retract servos during retracted or extended conditions. Make sure they are able to travel their full deflection. Overloading or stalling a servo can cause excessive current drain.
- Make sure all servos move freely through their rotations and no linkages hang up or bind. A binding control linkage can cause a servo to draw excessive current. A stalled servo can drain a battery pack in a matter of minutes.
- Correct any control surface “buzz” or “flutter” as soon as it is noticed in flight, as this condition can destroy the feedback potentiometer in the servo. It may be extremely dangerous to ignore such “buzz” or “flutter.”
- Use the supplied rubber grommets and brass servo eyelets when mounting your servos. Do not over-tighten the servo mounting screws, as this negates the dampening effect of the rubber grommets.
- Ensure the servo horn is securely fastened to the servo. Use only the servo arm screws provided; the size is different from other manufacturers.
- Discontinue to use servo arms when they become “yellowed” or discolored. Such servo arms may be brittle and can snap at any time, possibly causing the aircraft to crash.
- Check all related mounting screws and linkages frequently. Aircraft often vibrate, causing linkages and screws to loosen.

General Notes

Radio controlled models are a great source of pleasure. Unfortunately, they can also pose a potential hazard if not operated and maintained properly.

It is imperative to install your radio control system correctly. Additionally, your level of piloting competency must be high enough to ensure that you are able to control your aircraft under all conditions. If you are a newcomer to radio controlled flying, please seek help from an experienced pilot or your local hobby store.

Safety Do's and Don'ts for Pilots

- Ensure that your batteries have been properly charged prior to your initial flight.
- Keep track of the time the system is turned on so you will know how long you can safely operate your system.
- Perform a ground range check prior to the initial flight of the day. See the “Daily Flight Checks Section” for information.
- Check all control surfaces prior to each takeoff.
- Use frequency flags.
- Do not fly your model near spectators, parking areas or any other area that could result in injury to people or damage of property.
- Do not fly during adverse weather conditions. Poor visibility can cause disorientation and loss of control of your aircraft. Strong winds can cause similar problems.
- Do not fly unless your frequency is clear.

Warning: Only one transmitter at a time can operate on a given frequency. If you turn on your transmitter while someone else is operating a model on your frequency, both pilots will lose control of their models. Only one person can use a given frequency at a time. It does not matter if it is AM, FM or PCM—only one frequency at a time.

- Do not point the transmitter antenna directly toward the model. The radiation pattern from the tip of the antenna is inherently low.
- Do not take chances. If at any time during flight you observe any erratic or abnormal operation, land immediately and do not resume flight until the cause of the problem has been ascertained and corrected. Safety can never be taken lightly.

Federal Aviation Administration

Purpose

This advisory outlines safety standards for operations of model aircraft. We encourage voluntary compliance with these standards.

Background

Attention has been drawn to the increase in model aircraft operation. There is a need for added caution when operating free flight and radio controlled craft in order to avoid creating a noise nuisance or a potential hazard to full-scale aircraft and persons and/or property on the surface.

Operating Standards

Modelers generally are concerned with safety and exercise good judgment when flying model aircraft. However, in the interest of safer skies, we encourage operators of radio controlled and free flight models to comply with the following standards:

- a. Exercise vigilance in locating full-scale aircraft (get help if possible) so as not to create a collision hazard.
- b. Select an operating site at sufficient distance from populated areas so you do not create a noise problem or a potential hazard.
- c. Do not fly higher than 400 feet above the surface.
- d. Always operate more than three miles from the boundary of an airport unless you are given permission to be closer by the appropriate air traffic control facility in the case of an airport for which a control zone has been designated or by the airport manager in the case of other airports.
- e. Do not hesitate to ask for assistance in complying with these guidelines at the airport traffic control tower or air route traffic control center nearest the site of your proposed operation.

Information Provided By

Director, Air Traffic Service Federal Aviation Administration, Washington, D.C.

Daily Flight Checks

1. Check the battery voltage on both the transmitter and the receiver battery packs. Do not fly below 9.0V on the transmitter or below 4.7V on the receiver. To do so can crash your aircraft.

Note: When you check these batteries, ensure that you have the polarities correct on your expanded scale voltmeter.

2. Check all hardware (linkages, screws, nuts, and bolts) prior to each day's flight. Be sure that binding does not occur and that all parts are properly secured.
3. Ensure that all surfaces are moving in the proper manner.
4. Perform a ground range check before each day's flying session. The range check should be as follows:
 - Do not extend the transmitter antenna at this time. Turn the transmitter "on."
 - Turn the model "on."
 - Slowly walk away from the model while moving the control surfaces. The aircraft should function properly at a distance of 60–75 feet.
 - For PCM Only: With the throttle fail-safe preset to idle, bring the throttle slightly above idle. Walk away until the throttle drops to idle. This will be the distance of the range check.
5. Prior to starting your aircraft, turn off your transmitter, then turn it back on. Do this each time you start your aircraft. If any critical switches are on without your knowledge, the transmitter alarm will warn you at this time.
6. Check that all trim levers are in the proper location.
7. All servo pigtails and switch harness plugs should be secured in the receiver. Make sure that the switch harness moves freely in both directions.

Three Year Warranty Period

Exclusive Warranty- Horizon Hobby, Inc., (Horizon) warranties that the Products purchased (the "Product") will be free from defects in materials and workmanship for a period of 3 years from the date of purchase by the Purchaser.

Limited Warranty

(a) This warranty is limited to the original Purchaser ("Purchaser") and is not transferable. REPAIR OR REPLACEMENT AS PROVIDED UNDER THIS WARRANTY IS THE EXCLUSIVE REMEDY OF THE PURCHASER. This warranty covers only those Products purchased from an authorized Horizon dealer. Third party transactions are not covered by this warranty. Proof of purchase is required for warranty claims. Further, Horizon reserves the right to change or modify this warranty without notice and disclaims all other warranties, express or implied.

(b) Limitations- HORIZON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, ABOUT NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OF THE PRODUCT. THE PURCHASER ACKNOWLEDGES THAT THEY ALONE HAVE DETERMINED THAT THE PRODUCT WILL SUITABLY MEET THE REQUIREMENTS OF THE PURCHASER'S INTENDED USE.

(c) Purchaser Remedy- Horizon's sole obligation hereunder shall be that Horizon will, at its option, (i) repair or (ii) replace, any Product determined by Horizon to be defective. In the event of a defect, these are the Purchaser's exclusive remedies. Horizon reserves the right to inspect any and all equipment involved in a warranty claim. Repair or replacement decisions are at the sole discretion of Horizon. This warranty does not cover cosmetic damage or damage due to acts of God, accident, misuse, abuse, negligence, commercial use, or modification of or to any part of the Product. This warranty does not cover damage due to improper installation, operation, maintenance, or attempted repair by anyone other than Horizon. Return of any goods by Purchaser must be approved in writing by Horizon before shipment.

Damage Limits

HORIZON SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR PRODUCTION OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCT, WHETHER SUCH CLAIM IS BASED IN CONTRACT, WARRANTY, NEGLIGENCE, OR STRICT LIABILITY. Further, in no event shall the liability of Horizon exceed the individual price of the Product on which liability is asserted. As Horizon has no control over use, setup, final assembly, modification or misuse, no liability shall be assumed nor accepted for any resulting damage or injury. By the act of use, setup or assembly, the user accepts all resulting liability.

If you as the Purchaser or user are not prepared to accept the liability associated with the use of this Product, you are advised to return this Product immediately in new and unused condition to the place of purchase.

Law: These Terms are governed by Illinois law (without regard to conflict of law principals).

Safety Precautions

This is a sophisticated hobby Product and not a toy. It must be operated with caution and common sense and requires some basic mechanical ability. Failure to operate this Product in a safe and responsible manner could result in injury or damage to the Product or other property. This Product is not intended for use by children without direct adult supervision. The Product manual contains instructions for safety, operation and maintenance. It is essential to read and follow all the instructions and warnings in the manual, prior to assembly, setup or use, in order to operate correctly and avoid damage or injury.

Questions, Assistance, and Repairs

Your local hobby store and/or place of purchase cannot provide warranty support or repair. Once assembly, setup or use of the Product has been started, you must contact Horizon directly. This will enable Horizon to better answer your questions and service you in the event that you may need any assistance. For questions or assistance, please direct your email to productsupport@horizonhobby.com, or call 877.504.0233 toll free to speak to a service technician.

Inspection or Repairs

If this Product needs to be inspected or repaired, please call for a Return Merchandise Authorization (RMA). Pack the Product securely using a shipping carton. Please note that original boxes may be included, but are not designed to withstand the rigors of shipping without additional protection. Ship via a carrier that provides tracking and insurance for lost or damaged parcels, as **Horizon is not responsible for merchandise until it arrives and is accepted at our facility**. A Service Repair Request is available at www.horizonhobby.com on the "Support" tab. If you do not have internet access, please include a letter with your complete name, street address, email address and phone number where you can be reached during business days, your RMA number, a list of the included items, method of payment for any non-warranty expenses and a brief summary of the problem. Your original sales receipt must also be included for warranty consideration. Be sure your name, address, and RMA number are clearly written on the outside of the shipping carton.

Warranty Inspection and Repairs

To receive warranty service, you must include your original sales receipt verifying the proof-of-purchase date. Provided warranty conditions have been met, your Product will be repaired or replaced free of charge. Repair or replacement decisions are at the sole discretion of Horizon Hobby.

Non-Warranty Repairs

Should your repair not be covered by warranty the repair will be completed and payment will be required without notification or estimate of the expense unless the expense exceeds 50% of the retail purchase cost. By submitting the item for repair you are agreeing to payment of the repair without notification. Repair estimates are available upon request. You must include this request with your repair. Non-warranty repair estimates will be billed a minimum of ½ hour of labor. In addition you will be billed for return freight. Please advise us of your preferred method of payment. Horizon accepts money orders and cashiers checks, as well as Visa, MasterCard, American Express, and Discover cards. If you choose to pay by credit card, please include your credit card number and expiration date. Any repair left unpaid or unclaimed after 90 days will be considered abandoned and will be disposed of accordingly. **Please note: non-warranty repair is only available on electronics and model engines.**

Electronics and engines requiring inspection or repair should be shipped to the following address:

Horizon Service Center
4105 Fieldstone Road
Champaign, Illinois 61822

All other Products requiring warranty inspection or repair should be shipped to the following address:

Horizon Product Support
4105 Fieldstone Road
Champaign, Illinois 61822

Please call 877-504-0233 with any questions or concerns regarding this product or warranty.

Aircraft Programming Guide

MODEL NAME _____

MODEL NUMBER _____

	THRO NORM • REV	AILE NORM • REV	ELEV NORM • REV	RUDD NORM • REV	GEAR NORM • REV	FLAP NORM • REV	AUX2 NORM • REV
REVERSE SW							
SUB TRIM							
TRAVEL ADJUST	H %	L %	U %	L %	+ %	U %	U %
	L %	R %	D %	R %	- %	D %	D %

DUAL RATE • EXPO	0	D/R	AILE %	ELEV %	RUDD %
		EXP	%	%	%
	1	D/R	%	%	%
		EXP	%	%	%

ELEV – FLAP MIX	UP	%
	DOWN	%

AILE – RUDD MIX	RATE	%
	SW	

PROGRAM MIX		CHANNEL	SW	+POS	-POS	OFFSET
	MIX 1	–		%	%	
	MIX 2	–		%	%	
	MIX 3	–		%	%	
	MIX 4	–		%	%	
	MIX 5	–		%	%	
	MIX 6	–		%	%	

WING TYPE	FLAPERON	
	ELEVON	
	V-TAIL	

D/R SWITCH SELECT	AILERON	
	ELEVATOR	
	RUDDER	
	FLAP 2	
	FLAP 0	

FLAP SYSTEM	ELEV	%
	FLAP	

Helicopter Programming Guide

MODEL NAME _____

MODEL NUMBER _____

	THRO	AILE	ELEV	RUDD	GEAR	PITCH	AUX2
REVERSE SW	R • N	R • N	R • N	R • N	R • N	R • N	R • N
SUB TRIM							
TRAVEL ADJUST	H %	L %	U %	L %	+ %	H %	H %
	L %	R %	D %	R %	- %	L %	L %

THROTTLE CURVE		P-LOW	P-1	P-MID	P-3	P-HIGH
	NORMAL					
	STUNT 1					
	STUNT 2					

THROTTLE HOLD	ON •	POSITION
	OFF	

PITCH CURVE		P-LOW	P-1	P-MID	P-3	P-HIGH
	NORMAL					
	STUNT 1					
	STUNT 2					

SWASH TYPE	NORMAL	90 CCPM	120 CCPM	180 CCPM
------------	--------	---------	----------	----------


SWASH MIX	AILE	ELEV	PITCH
	%	%	%
	REV R•N	REV R•N	REV R•N

SWITCH SELECT	D/R	
	GEAR	
	FL-M	

PROGRAM MIX		CHANNEL	SW	+POS	-POS	OFFSET
	MIX 1	-		%	%	
	MIX 2	-		%	%	
	MIX 3	-		%	%	

DUAL RATE • EXPO	0		AILE	ELEV	RUDD
		D/R	%	%	%
	EXP	%	%	%	
	1	D/R	%	%	%
		EXP	%	%	%

REVO MIX	NORMAL	UP	%
		DOWN	%
	STUNT	UP	%
		DOWN	%



SPEKTRUM®

HORIZON  **HOBBY**

© 2006 Horizon Hobby, Inc.
4105 Fieldstone Road
Champaign, Illinois 61822
(877) 504-0233
www.horizonhobby.com
www.spektrumrc.com